


rXone V3

Spec Sheet

500 x 500 mm

ULTRA RIGID TECHNOLOGY
FRONTSERVICE
BLACK-FACE
QUICK-LOCK-SYSTEM
MAGNETIC FAST-RIGG
VACUUM MAINTENANCE TOOL
CLIMBABLE FRAME
FAST REPLACEABLE BACKBOX



Pixelpitch	1,9 mm
Brightness	≥ 1.000 nit (1.200 nits uncalibrated)
Weight	11,8 kg
Power Consumption	Nominal 60 W max. 160 W
SMD-Type	Nationstar 1515
SMD Specifications	High-Brightness, Ultra Rigid Technology
Color Depth	Up to 18+ Bit per color channel
Resolution	256 x 256 px
LED Driver	MBI5253
Receivingcard	Novastar A10S+N
Scanmode	1/32
Refreshrate	≥ 2.880 Hz
Horiz. Angle of View	+85° -85°
Vert. Angle of View	+85° -85°
Contrast	> 5.000:1
Voltage Range	AC 88-264V 50 Hz
Connection	powerCON TRUE1
Dimensions (BxHxT)	500 x 500 mm T = 100 mm
IP Rating	IP 54 (Front & Back)
Temperature Rating	-30°C to +45°C (In Operation) -10°C to +55°C (Storing)
Highlights	Ultra Rigid Technology, Frontservice, Quick-Lock-System, Magnetic Fast-Rigg, Climbable Frame, Fast Replaceable Backbox
Certification	   