


rXone+

Spec sheet 500 x 500 mm

ULTRA RIGED TECHNOLOGY
FRONTSERVICE
BLACK-FACE
QUICK-LOCK-SYSTEM
MAGNETIC FAST-RIGG
VACUUM MAINTENANCE TOOL
CLIMBABLE FRAME
FAST REPLACEABLE BACKBOX



Pixelpitch	1,25 mm
Brightness	≥ 900 nits
Weight	12,5 kg
Power Consumption	Nominal 70 W max. 160 W
SMD-Type	LEDitgo BF1010 URT 3-in-1 RGB
SMD Specifications	High-Brightness, Ultra Rigid Technology
Color Depth	Up to 16 Bit
Resolution	400 x 400 px
LED Driver	MBI5264
Receivingcard	Brompton R2+
Scanmode	1/25
Refreshrate	≥ 3.840 Hz
Horiz. Angle of View	+170° -170°
Vert. Angle of View	+170° -170°
Contrast	> 5.000:1
Voltage Range	AC 88-264V 50-60 Hz
Connection	Neutrik powerCON TRUE1 TOP
Dimensions (BxHxT)	500 x 500 mm T = 100 mm
IP Rating	IP 43 (Front & Back)
Temperature Rating	-10°C to +40°C (In Operation) -20°C to +60°C (Storing)
Highlights	Ultra Rigid Technology, Frontservice, Quick-Lock-System, Magnetic Fast-Rigg, Climbable Frame, Fast Replacable Backbox
Certification	   