

RA193ix Flex

Spec Sheet

496 x 496 mm

NOVASTAR A10S PRO RECEIVINGCARD
URT TECHNOLOGY
QUICK-LOCK-SYSTEM
MAGNETIC FAST-RIGG
CURVING UP TO +/- 45°



Pixelpitch	1,93 mm
Brightness	≥ 800 - 1.000 nits
Weight	9,3 kg
Power Consumption	Nominal 48 W max. 200 W
SMD-Type	GOB
SMD Specifications	High-Level, Black-Face
Color Depth	22 Bit
Resolution	256 x 256 px
LED Driver	CFD955
Receivingcard	Novastar A10s Pro
Scanmode	1/32
Refreshrate	≥ 3.840 Hz
Horiz. Angle of View	+160° -160°
Vert. Angle of View	+160° -160°
Contrast	> 6.000:1
Voltage Range	AC 100-240V 50 Hz
Connection	Seetronic TR1
Dimensions (BxHxT)	496 x 496 x 55 mm
IP Rating	IP 40
Temperature Rating	-15°C to +40°C (In Operation) -20°C to +45°C (Storing)
Highlights	Adjustable on both sides to concave and convex in steps of 0, 2.5, 5, 7.5, 10, 12.5, 15, 17.5, 20, and 22.5°, with a minimum diameter of 1.27 m

Certification

