

# DH-4,8E

## Spec sheet

500 x 1.000 mm

ICND2153S DRIVER IC  
3.840HZ REFRESHRATE  
FAST REPLACEABLE BACKBOX  
FRONT- & BACKSERVICE



|                             |                                                           |
|-----------------------------|-----------------------------------------------------------|
| <b>Pixelpitch</b>           | 4,80 mm                                                   |
| <b>Brightness</b>           | ≥ 5.500 nits                                              |
| <b>Weight</b>               | 12,8 kg                                                   |
| <b>Power Consumption</b>    | Nominal 80 W   max. 320 W                                 |
| <b>SMD-Type</b>             | SMD1921                                                   |
| <b>SMD Specifications</b>   | High Brightness, High Contrast, High Level                |
| <b>Color Depth</b>          | Up to 16 Bit                                              |
| <b>Resolution</b>           | 104 x 208 px                                              |
| <b>LED Driver</b>           | ICND2153S                                                 |
| <b>Receivingcard</b>        | Novastar A5s+                                             |
| <b>Scanmode</b>             | 1/8                                                       |
| <b>Refreshrate</b>          | ≥ 3.840 Hz                                                |
| <b>Horiz. Angle of View</b> | +140°   -140°                                             |
| <b>Vert. Angle of View</b>  | +140°   -140°                                             |
| <b>Contrast</b>             | > 3.600:1                                                 |
| <b>Voltage Range</b>        | AC 210-240V   50-60 Hz                                    |
| <b>Connection</b>           | Seetronic                                                 |
| <b>Dimensions (BxHxT)</b>   | 500 x 1.000 x 80 mm                                       |
| <b>IP Rating</b>            | IP 65                                                     |
| <b>Temperature Rating</b>   | -20°C to +50°C (In Operation)<br>-10°C to +40°C (Storing) |
| <b>Highlights</b>           | Fast replaceable backbox, 100% front- and backservice     |

### Certification




 EMC

Stand: 07/2025