

DH-4,8HB

Spec Sheet

500 x 1.000 mm

HIGH BRIGHTNESS
GOLD WIRE
ICND2153S DRIVER IC
3.840HZ REFRESHRATE
FAST REPLACEABLE BACKBOX
FRONT- & BACKSERVICE



Pixelpitch	4,80 mm
Brightness	≥ 8.500 nits
Weight	12,8 kg
Power Consumption	Nominal 85 W max. 340 W
SMD-Type	SMD1921 gold wire
SMD Specifications	High Brightness, High Contrast, High Level
Color Depth	Up to 16 Bit
Resolution	104 x 208 px
LED Driver	ICND2153S
Receivingcard	Novastar A5s+
Scanmode	1/8
Refreshrate	≥ 3.840 Hz
Horiz. Angle of View	+140° -140°
Vert. Angle of View	+140° -140°
Contrast	> 3.600:1
Voltage Range	AC 210-240V 50-60 Hz
Connection	Seetronic
Dimensions (BxHxT)	500 x 1.000 x 80 mm
IP Rating	IP 65
Temperature Rating	-20°C to +50°C (In Operation) -10°C to +40°C (Storing)
Highlights	Fast replaceable backbox, 100% front- and backservice

Certification




 EMC

Stand: 07/2025