

# TX1,5-C

## Spec sheet

600 x 337,5 mm

COB TECHNOLOGY  
NOVASTAR A10S PRO RECEIVINGCARD  
5G READY  
DRIVER ICND1069



|                             |                                                               |
|-----------------------------|---------------------------------------------------------------|
| <b>Pixelpitch</b>           | 1,56 mm                                                       |
| <b>Brightness</b>           | ≥ 1.200 nits                                                  |
| <b>Weight</b>               | 4,8 kg                                                        |
| <b>Power Consumption</b>    | Nominal 31 W   max. 90 W                                      |
| <b>SMD-Type</b>             | COB 1,56                                                      |
| <b>SMD Specifications</b>   | High Brightness, High Contrast, High Level                    |
| <b>Color Depth</b>          | Up to 14 Bit                                                  |
| <b>Resolution</b>           | 384 x 216 px                                                  |
| <b>LED Driver</b>           | ICND1069                                                      |
| <b>Receivingcard</b>        | Novastar A10S pro                                             |
| <b>Scanmode</b>             | 1/54                                                          |
| <b>Refreshrate</b>          | ≥ 3.840 Hz                                                    |
| <b>Horiz. Angle of View</b> | +160°   -160°                                                 |
| <b>Vert. Angle of View</b>  | +140°   -140°                                                 |
| <b>Contrast</b>             | > 10.000:1                                                    |
| <b>Voltage Range</b>        | AC 210-240V   50-60 Hz                                        |
| <b>Connection</b>           | direct wiring                                                 |
| <b>Dimensions (BxHxT)</b>   | 600 x 337,5 x 40 mm                                           |
| <b>IP Rating</b>            | IP 41                                                         |
| <b>Temperature Rating</b>   | -20°C to +50°C (In Operation)<br>-10°C to +40°C (Storing)     |
| <b>Highlights</b>           | COB Technologie, Novastar A10S Pro<br>Receivingcard, 5G Ready |

### Certification



Stand: 02/2025